

Thervan Loading ramps



 **THERVAN**



Technical specifications

- Load capacity 10.000 kg
- Length 12 m
- Horizontal platform 2.50 m
- Total width 2.28 m
- Driving width 1.88 m
- Lip width 2.12 m
- Tread with galvanized antiskid grids
- Hydraulic height adjustment from 98 up to 170 cm
- Weight: 4 Tons
- CE compliant (machine directive)
- Pump control on the side
- Four solid rubber wheels
- Coupling to move the ramp by means of a lift truck
- Sandblasted against rust formation
- Colour: Blue



Loading Ramps Accessories



1 SAFETY JACK
REF 107TA8319
Capacity: 22700kg
Support capacity: 45500kg
Height: 1070-1350mm
Weight: 56kg

2 WHEEL CHOCK
REF 116TA6235
Length: 300mm
Height: 203mm
Width: 188mm
Weight/unit: 3.15kg


3 SAFETY TRESTLE
REF 124TA2106
Capacity: 15 ton
Length: 1200mm
Height: 1080 - 1300mm
Width: 550mm
Wheels: rubber 200mm
Weight: 70kg
5 Adjustable Heights



CHOCK 1,5 T
REF 105TA4044



CHOCK 5 T
REF 105TA4045



CHOCK 6,5 T
REF 105TA4048



CHOCK 20 T
REF 106TA6391



THERMOT & VANHALST NV • EQUIPMENT DIVISION
Brabantstraat 15 • BE-8790 Waregem
T +32 56 43 43 11 • F +32 56 43 43 45 • forklift@tvh.com • www.tvh.com